

BUY ONLINE

FREE CATALOG

SAVE UP TO 25%



DATA BULLETIN

Synthetic V-Twin Transmission Fluid

AMSOIL Synthetic V-Twin Transmission Fluid is specifically designed for bikers who prefer a dedicated transmission fluid over a multi-use lubricant. Its frictional properties deliver smooth shifts and it helps quiet transmission noise, letting riders focus on enjoying the ride. AMSOIL Synthetic V-Twin Transmission Fluid is Warranty Secure™ and will not void your motorcycle's warranty. It is a cost-effective, high-performance alternative to original equipment manufacturer (OEM) fluids.

Promotes Quiet Operation

AMSOIL Synthetic V-Twin Transmission Fluid forms a durable oil film on bearings and gears, helping to dampen loud thunks when shifting and reduce gear noise.

Protects Against Gear and Bearing Wear

Extreme pressures between gear teeth can shear inferior transmission fluids, reducing viscosity and compromising wear protection. AMSOIL Synthetic V-Twin Transmission Fluid resists viscosity loss due to shear and withstands extreme heat for excellent wear protection. Its robust molecules provide film strength to protect against damage from shock loading, while its extreme-pressure additives deliver additional protection against wear.

Delivers Smooth Shifts

AMSOIL Synthetic V-Twin Transmission Fluid's finely tuned viscometrics and frictional properties provide smooth shifts, helping riders avoid missed shifts for crisp acceleration through each gear. It provides riders confidence that their transmission is going to respond as intended for an improved ride.



- **Protects** against gear and bearing wear
- **Delivers** smooth shifts
- **Helps** eliminate loud thunks and gear noise

All trademarked names and images are the property of their respective owners and may be registered marks in some countries. No affiliation or endorsement claim, express or implied, is made by their use. All products advertised here are AMSOIL-engineered for use in the applications shown.

Order by Phone 1-800-956-5695 - Give Operator Reference #5372670

TYPICAL TECHNICAL PROPERTIES
AMSOIL Synthetic V-Twin Transmission Fluid (MVT)

Table with 2 columns: Property and Value. Properties include Kinematic Viscosity @ 100°C, Kinematic Viscosity @ 40°C, Viscosity Index, Pour Point, Flash Point, Fire Point, Four-Ball Wear Test, NOACK Volatility, and Foam.

APPLICATIONS

Engineered for use in Harley-Davidson®, Triumph® and pre-2013 INDIAN® bikes.

RECOMMENDATIONS

AMSOIL Synthetic V-Twin Transmission Fluid is recommended for up to 20,000 miles or one year, whichever comes first.

WARRANTY SECURE™

AMSOIL Synthetic V-Twin Transmission Fluid is Warranty Secure, keeping your factory warranty intact. AMSOIL Synthetic V-Twin Transmission Fluid is a high-performance replacement for vehicle manufacturer-branded products and is also backed by the AMSOIL Limited Warranty (G1363). For details, visit www.amsoil.com/warrantysecure.



All trademarked names are the property of their respective owners and may be registered marks in some countries. No affiliation or endorsement claim, express or implied, is made by their use.



AMSOIL products and Dealership information are available from your local full-service AMSOIL Dealer.